



# JMA Wireless DAS Platform (US Region)

RD35BWX2AT

RD35BWX2DT

**Next Generation, MIMO, Single-band, Ultra-high-power, Software-defined Remote Units (SDRU) Operating in the 3450-3550MHz Frequency Range**



## Product Classification

|                              |                                   |
|------------------------------|-----------------------------------|
| <b>Regional Availability</b> | US                                |
| <b>Product Type</b>          | MIMO Software-Defined Remote Unit |
| <b>Product Brand</b>         | JMA DAS                           |

## General Specifications

|                         |  |
|-------------------------|--|
| <b>Cooling</b>          | Fan Cooled   |
| <b>Connector Type</b>   | LC-UPC optical connector, 4.3-10(f) RF connector   |
| <b>Power Class</b>      | SDRU Ultra-high Power  |
| <b>Powering Type</b>    | AC, DC options available   |
| <b>Size</b>             | 453x405x198mm (17.8x15.9x7.8in) max volume - wall-mount bracket and optical port protection included |
| <b>Enclosure Rating</b> | IP66/Type 4X enclosure   |

## Supported Bands

|             |              |
|-------------|--------------|
| <b>Band</b> | 3450-3550MHz |
|-------------|--------------|

Please contact your local JMA representative for detailed specifications