




UXP-4F-12S-01

4.3-10 Female Connector for 1/2" Superflexible Cable



[Installation video](#)



[Installation instructions](#)



Contact technical support:
1-888-201-6073
techsupport@jmawireless.com

General	Specification																																			
Interface/gender	4.3-10 Female																																			
Cables supported¹	<table border="1"> <thead> <tr> <th>Manufacturer</th> <th>P/N</th> <th>Manufacturer</th> <th>P/N</th> </tr> </thead> <tbody> <tr> <td>JMA Wireless</td> <td>JMA12S-50</td> <td>Eupen</td> <td>EC4HF</td> </tr> <tr> <td rowspan="3">CommScope</td> <td>FSJ4</td> <td>Leoni Flexline</td> <td>1/2"S</td> </tr> <tr> <td>FSJ4RK</td> <td rowspan="2">LS/Superior Essex</td> <td>HFSC 12D</td> </tr> <tr> <td>FSJ4RN-50</td> <td>FSC12DPV</td> </tr> <tr> <td>RFS</td> <td>HS4RP</td> <td rowspan="2">Hansen</td> <td>RF5012S</td> </tr> <tr> <td>NK Draka</td> <td>SCF12</td> <td>RF5012SZ</td> </tr> <tr> <td>Rosenbeger</td> <td>RFF1200</td> <td>HUBER+SUHNER</td> <td>SF 1/2 HF</td> </tr> <tr> <td></td> <td>SL 1/2" S</td> <td rowspan="2">Wireless Supply</td> <td>WS12/SF</td> </tr> <tr> <td></td> <td></td> <td>WS12/SF/WP</td> </tr> </tbody> </table>	Manufacturer	P/N	Manufacturer	P/N	JMA Wireless	JMA12S-50	Eupen	EC4HF	CommScope	FSJ4	Leoni Flexline	1/2"S	FSJ4RK	LS/Superior Essex	HFSC 12D	FSJ4RN-50	FSC12DPV	RFS	HS4RP	Hansen	RF5012S	NK Draka	SCF12	RF5012SZ	Rosenbeger	RFF1200	HUBER+SUHNER	SF 1/2 HF		SL 1/2" S	Wireless Supply	WS12/SF			WS12/SF/WP
	Manufacturer	P/N	Manufacturer	P/N																																
	JMA Wireless	JMA12S-50	Eupen	EC4HF																																
	CommScope	FSJ4	Leoni Flexline	1/2"S																																
		FSJ4RK	LS/Superior Essex	HFSC 12D																																
		FSJ4RN-50		FSC12DPV																																
	RFS	HS4RP	Hansen	RF5012S																																
	NK Draka	SCF12		RF5012SZ																																
	Rosenbeger	RFF1200	HUBER+SUHNER	SF 1/2 HF																																
	SL 1/2" S	Wireless Supply	WS12/SF																																	
			WS12/SF/WP																																	
Weight	0.334 lb 151.5 g																																			
JMA Weather Protection System	N/A																																			

Tools required	JMA part number	Comment
Cable preparation	SP-12S-01	COR12S-01
Connector compression	HCG-FRAMESET-1/2, HCG-CC	Insert D
Hex width	23 mm 0.9 in.	

Frequency band		VSWR		Return loss (dB)	
Foam Dielectric	Air Dielectric	Foam Dielectric	Air Dielectric	Foam Dielectric	Air Dielectric
DC-1000 MHz	555-1000 MHz	1.02	1.02	40	40
1000-2000 MHz	1000-2700 MHz	1.03	1.03	36	36
2000-4000 MHz	2700-3800 MHz	1.05	1.07	32	29
4000-6000 MHz	3800-6000 MHz	1.08	1.15	28	23

Electrical	Specification	Comment
Connector impedance	50 ohm	
Operating frequency band	DC-6 GHz	
3rd order IMD dynamic, (PIM)	-161 dBc, typical	IEC 62037-2, -3
DC test voltage	2500 V	
Center contact resistance	≤ 0.8 milliohm	
Outer contact continuity	1.5 milliohm max.	
Average power	600 W @ 900 MHz	
Peak power, max.	15 kW	
Insertion loss, typical	0.05 dB	Per connector
Shielding effectiveness	< -120 dB	@ 0-1 GHz

Mechanical	Specification	Comment
Pull force combined	.78 kN > 175 lb	Cable limited
Cable retention torque	6.7 N·m 5 lbf·ft	Cable limited
Interface durability	100 cycles	IEC 61169-4:9.5

¹For cable types not listed, please contact JMA Technical Support.





UXP-4F-12S-01

4.3-10 Female Connector for 1/2" Superflexible Cable

Environmental	Specification	Test
Operating temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Storage temperature	-55 °C to +85 °C (-67 °F to 185 °F)	
Accelerated UV	1000 hr	ASTM G154
Immersion test method	Mated & unmated, IP68	IEC 60529:2001 & ANSI/SCTE 60
Water jetting test method	Mated & unmated, IP66	IEC 60529:2001
Mechanical shock test method	Pass	IEC 60068-2-27
Thermal shock test method	Pass	IEC 60068-2-14
Vibration test method	100 m/s ² , 2 Hz to 200 Hz	IEC 61169-1:2003
Corrosion test method	1000 hr	IEC 60068-2-11

05/29/24