

AXP20-FRO33

X-Pol Antenna, 1710-2170 MHz, (50.5", 33° H-Beam)


- Fast Roll Off (FRO)
- Designed to improve SNR
- Greatly increases LTE data rates
- Macro Cell High Gain Antenna
- Highly Reliable Fixed Tilt Design
- Suitable for LTE/CDMA/UMTS/GSM
- Mechanical Tilt Bracket Included



Available with Integrated Diplexers

Reduces mainline cables

Eliminates External Tower Devices



ELECTRICAL SPECIFICATIONS

Frequency Band, MHz	1710-1880	1850-1990	1920-2170
Horizontal Beam Width, 3dB points	33°		
Gain, dBi	19.7	20.0	20.3
Vertical Beam Width, 3dB points	7°		
Front-to-Back at 180°, dB	>30		
Upper Side Lobe Suppression, Typical, dB	<-18		
Polarization	+/-45°		
Electrical Down Tilt, Fixed	0, 2, 4, 6°		
VSWR/Return Loss, dB, Maximum	1.5:1/-14.0		
Return Loss, Pass Thru, dB, Maximum	-17.7		
Isolation Between Ports, dB, Minimum	28		
Intermodulation (2x20w), IM3, dBc, Maximum	-150		
Impedance, ohms	50		
Maximum Power Per Connector, CW	250 @ 1900 MHz		

MECHANICAL SPECIFICATIONS

Dimensions, Length/Width/Depth	50.5/12.5/7.1 in. (1282/318/180mm)
Connector (Quantity)	(2 or 4) 7-16 DIN Female
Connector Torque	220-265 lbf-in (23-30 N-m)
Connector Location	Back
Antenna Weight	20.0 lbs (9.1 kg) <i>Note: Weight varies slightly based on ordering options</i>
Bracket Weight	13.2 lb. (6.0 kg)
Standard Bracket Kit	CSS P/N 919011 (Included)
Mechanical Down Tilt Range	0-12°
Radome Material	High Strength Luran, UV Stabilized, ASTM D1925
Wind Survival	150 mph (241 km/h)
Front Wind Load	127.1 lbf (565.3 N) @100mph
Equivalent Flat Plate	2.53 sq-ft (c=2) @ 100mph

ORDER INFORMATION

MODEL	DESCRIPTION
AXP20-FRO33- x	X-Pol antenna with two back DIN connectors
AXP20-FRO33- x -IP	X-Pol antenna with four back DIN connectors with integrated diplexers
919036	Optional Bracket Kit, 2-Point, 12deg D-tilt, For 4.5" OD Pole

x defines the electrical tilt