

# WPS-7

Weather Protection System  
1-5/8" to 1/2" Connections



General	Specification	Comment
Cables Supported	Andrew	AL7-50, AVA7-50, LDF7-50, VXL7-50
	RFS	LCF158-50JA, LCF158-50J
	EUPEN	EC7-50A
	DRAKA	RFA 1-5/8"-50 (NKRF 15800)
	LEONI	Flexline 1-5/8" R
	LS	LHF 42D
	CommScope	FXL1873, CR1873
Weight / Dimensions	.64 lbs   290 g	5.00" (127 mm) X 3.20" (81.3 mm)
Material	1-5/8" - Silicone Rubber 1-5/8" to 1/2" Adapter- U.V. Stable ABS	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation Temperature Operating Temperature Storage Temperature	-40°C to +65°C -40°C to +65°C -55°C to +85°C	
Moisture Resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion Resistance	1000 Hours	ASTM B117
U.V. Resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 Hours	