

# WPS-NRA-1S

JMA Wireless Weather Protection System™



## Weather Protection System 1/4" N, 4.1-9.5, and 4.3-10 Right Angle Superflex



General	Specification	Comment
<b>Cables supported</b>	Andrew FSJ1-50A, FSJ1RK-50B, PTS1-50-P; RFS SCF14-50J, SCF14-50JFN; Hansen RF5014S, RF5014SZ; Eupen EC1-50-HF; Times SPP-250-LLPL	
<b>Weight / dimensions</b>	.10 lb   46.1 g	3.33 in [84.6 mm] x 2.28 in [58 mm]
<b>Material</b>	Silicone rubber	
<b>Lubricant</b>	Dow Corning Molykote® III	
<b>Reusability</b>	Unlimited	

Environmental	Specification	Comment
<b>Installation temperature</b> <b>Operating temperature</b> <b>Storage temperature</b>	-40 °C to +65 °C -40 °C to +65 °C -55 °C to +85 °C	
<b>Moisture resistance</b>	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
<b>Corrosion resistance</b>	1000 hours	ASTM B117
<b>U.V. resistance</b>	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
<b>H.A.L.T.</b>	40 hours	