

WPS-NRA-4S

JMA Wireless Weather Protection System™

Weather Protection System 1/2" N, 4.1-9.5, and 4.3-10 Right Angle Superflexible



General	Specification	Comment
Cables supported	Andrew FSJ4, FSJ4RK; RFS SCF12; NK Draka RFF1200; Eupen EC4HF; Leoni Flexline 1/2"S; LS/Superior Essex HFSC 12D; Hansen RF5012S, RF5012SZ; Rosenbeger SL 1/2" S; HUBER+SUHNER SF 1/2 HF	
Weight / dimensions	.11 lb 49.9 g	4.06 in. [103.2 mm] x 2.31 in. [58.7 mm]
Material	Silicone rubber	
Lubricant	Dow Corning Molykote® III	
Reusability	Unlimited	

Environmental	Specification	Comment
Installation temperature Operating temperature Storage temperature	-40 °C to +65 °C -40 °C to +65 °C -55 °C to +85 °C	
Moisture resistance	No leakage	ANSI/SCTE 60 2004, IP-67, IP-68
Corrosion resistance	1000 hours	ASTM B117
U.V. resistance	Exposure to UV light for 1000 hours per ASTM G 53 using UVB-313 type lamps	
H.A.L.T.	40 hours	