


C7C-FRO-656


C-Pol Antenna, 698-896 MHz, (72.0", 56° H-Beam)

- Designed to improve SNR
- Greatly increases LTE data rates
- Macro Cell High Gain Antenna
- Highly Reliable Fixed Tilt Design
- Suitable for LTE/CDMA/UMTS/GSM
- Mechanical Tilt Bracket Included



Available with Integrated Diplexers

- Reduces mainline cables
- Eliminates External Tower Devices
- Supports high band TMAs



ELECTRICAL SPECIFICATIONS		
Frequency Band, MHz	698-824	824-896
Horizontal Beam Width, 3dB points	59°	55°
Gain, dBi	15.4	16.3
Vertical Beam Width, 3dB points	12.0°	10.5°
Front-to-Back at 180°, dB	>29	
Upper Side Lobe Suppression, Typical, dB	<-18	
Polarization	CIRCULAR	
Electrical Down Tilt, Fixed	0, 2°	
VSWR/Return Loss, dB, Maximum – Non IP	1.35:1/-16.5	
VSWR/Return Loss, dB, Maximum – With IP	1.5:1/-14.0	
Return Loss, dB Maximum, Pass Thru	-17.7	
Isolation Between Ports, dB, Minimum (745-756 MHz)	24	
Intermodulation (2x20w), IM3, dBc, Maximum	-150	
Impedance, ohms	50	
Maximum Power Per Connector, CW	500 @ 800 MHz	

MECHANICAL SPECIFICATIONS

Dimensions, Length/Width/Depth	72.0/14.6/7.1 in. (1829/372/181mm)
Connector (Quantity)	(2 or 4) 7-16 DIN Female
Connector Torque	220-265 lbf-in (23-30 N-m)
Connector Location	Back
Antenna Weight	32.2 lbs (14.6 kg) <i>Note: Weight varies slightly based on ordering options</i>
Bracket Weight	13.2 lb. (6.0 kg)
Standard Bracket Kit	CSS P/N 919011 (Included)
Mechanical Down Tilt Range	0-12°
Radome Material	High Strength Luran, UV Stabilized, ASTM D1925
Wind Survival	150 mph (241 km/h)
Front Wind Load	211.6 lbf (941.4 N) @100mph
Equivalent Flat Plate	4.22 sq-ft (c=2) @ 100mph

ORDER INFORMATION

MODEL	DESCRIPTION
C7C-FRO-656- x	C-Pol antenna with two back DIN connectors
C7C-FRO-656- x -IP	C-Pol antenna with four back DIN connectors with integrated pass thru diplexers
919036	Optional Bracket Kit, 2-Point, 12deg D-tilt, For 4.5" OD Pole

x defines the electrical tilt