

X7C-880


X-Pol Antenna, 698-896 MHz, (96.0", 80° H-Beam)

- Macro Cell High Gain Antenna
- Broadband Radiators
- Highly Reliable Fixed Tilt Design
- Suitable for LTE/CDMA/UMTS/GSM
- Mechanical Tilt Bracket Included



Available with Integrated Diplexers

- Reduces mainline cables
- Eliminates External Tower Devices
- Supports high band TMAs



ELECTRICAL SPECIFICATIONS		
Frequency Band, MHz	698-824	824-896
Horizontal Beam Width, 3dB points	80°	
Gain, dBi	16.1	
Vertical Beam Width, 3dB points	7.9°	
Front-to-Back at 180°, dB	>28	
Upper Side Lobe Suppression, Typical, dB	<-18	
Polarization	+/-45°	
Electrical Down Tilt, Fixed	0, 2, 4, 6, 8, 10°	
VSWR/Return Loss, dB, Maximum	1.5:1/-14.0	
Return Loss, dB Maximum, Pass Thru	-17.7	
Isolation Between Ports, dB, Minimum	28	
Intermodulation (2x20w), IM3, dBc, Maximum	-150	
Impedance, ohms	50	
Maximum Power Per Connector, CW	500 @ 800 MHz	

MECHANICAL SPECIFICATIONS

Dimensions, Length/Width/Depth	96.0/12.5/7.1 in. (2438/318/180mm)
Connector (Quantity)	(2 or 4) 7-16 DIN Female
Connector Torque	220-265 lbf-in (23-30 N-m)
Connector Location	Back or Bottom
Antenna Weight	40.0 lbs (18.1 kg) <i>Note: Weight varies slightly based on ordering options</i>
Bracket Weight	18.2 lb. (8.3 kg)
Standard Bracket Kit	CSS P/N 919032 (Included)
Mechanical Down Tilt Range	0-6°
Radome Material	High Strength Luran, UV Stabilized, ASTM D1925
Wind Survival	150 mph (241 km/h)
Front Wind Load	241.6 lbf (1074.7 N) @100mph
Equivalent Flat Plate	4.81 sq-ft (c=2) @ 100mph

ORDER INFORMATION

MODEL	DESCRIPTION
X7C-880- x	X-Pol antenna with two back DIN connectors
X7C-880- x -IP	X-Pol antenna with four back DIN connectors with integrated pass thru diplexers
X7C-880- x -B	X-Pol antenna with two bottom DIN connectors
X7C-880- x -IP-B	X-Pol antenna with four bottom DIN connectors with integrated pass thru diplexers
919049	Optional Bracket Kit, 3-Point, 6deg D-tilt, For 4.5" OD Pole

x defines the electrical tilt