


X7C-FRO-640

X-Pol Antenna, 698-896 MHz, (72.0", 40° H-Beam)

- Fast Roll Off (FRO)
- Designed to improve SNR
- Greatly increases LTE data rates
- Macro Cell High Gain Antenna
- Highly Reliable Fixed Tilt Design
- Suitable for LTE/CDMA/UMTS/GSM
- Mechanical Tilt Bracket Included




Available with Integrated Diplexers

Reduces mainline cables

Eliminates External Tower Devices

Supports high band TMAs



ELECTRICAL SPECIFICATIONS

Frequency Band, MHz	698-824	824-896
Horizontal Beam Width, 3dB points	40°	
Gain, dBi	18.0	18.8
Vertical Beam Width, 3dB points	11°	
Front-to-Back at 180°, dB	>30	
Upper Side Lobe Suppression, Typical, dB	<-18	
Polarization	+/-45°	
Electrical Down Tilt, Fixed	0, 2, 4, 6, 8, 10°	
VSWR/Return Loss, dB, Maximum	1.5:1/-14.0	
Return Loss, dB Maximum, Pass Thru	-17.7	
Isolation Between Ports, dB, Minimum	28	
Intermodulation (2x20w), IM3, dBc, Maximum	-150	
Impedance, ohms	50	
Maximum Power Per Connector, CW	500 @ 800 MHz	

MECHANICAL SPECIFICATIONS

Dimensions, Length/Width/Depth	72.0/18.8/8.9 in. (1829/478/226mm)
Connector (Quantity)	(2 or 4) 7-16 DIN Female
Connector Torque	220-265 lbf-in (23-30 N-m)
Connector Location	Back
Antenna Weight	28.0 lbs (12.7 kg) <i>Note: Weight varies slightly based on ordering options</i>
Bracket Weight	13.2 lb. (6.0 kg)
Standard Bracket Kit	CSS P/N 919011 (Included)
Mechanical Down Tilt Range	0-12°
Radome Material	High Strength Luran, UV Stabilized, ASTM D1925
Wind Survival	150 mph (241 km/h)
Front Wind Load	233.6 lbf (1039.1 N) @100mph
Equivalent Flat Plate	4.65 sq-ft (c=2) @ 100mph

ORDER INFORMATION

MODEL	DESCRIPTION
X7C-FRO-640- X	X-Pol antenna with two back DIN connectors
X7C-FRO-640- X -IP	X-Pol antenna with four back DIN connectors with integrated pass thru diplexers
919036	Optional Bracket Kit, 2-Point, 12deg D-tilt, For 4.5" OD Pole

X defines the electrical tilt